

VERTICUS®

3, 4 AND 5-STAGE ENCLOSED HIGH PRESSURE BREATHING AIR COMPRESSORS

The days of “Breadbox” designed compressor packages are over! Step up to the BAUER VERTICUS. The updated sound attenuated cabinet is equipped with a unique aesthetically pleasing horizontally hinged, and gas shock supported, operations panel, assuring direct and easy access to the drive belts. Vertically hinged and lift-off side maintenance access doors incorporating fast pin technology make removal of the doors a snap – no hand tools are required! The rear panel incorporates integral handles and tabbed lift off design. The front vertically hinged access door is affixed with a hex keyed latch to eliminate the accidental opening of the door while the system is operating. Sound attenuation has been incorporated on every possible panel to provide a nice and quiet operating level of approximately 72 DB (within one-meter). One package size accommodates BAUER high pressure aircooled compressors from 5 to 20 HP motors. Our new, larger, 7” HMI enhances monitoring of system functions.

› **PRESSURE:**

Up to 6000 PSIG
(414 BAR)

› **CHARGING RATE:**

5 to 13 SCFM
(142 to 368 L/MIN)

› **POWER:**

5 to 10 HP (3.7 to 7.5 kW)



› VERTICUS

STANDARD SCOPE OF SUPPLY

- › BAUER breathing air purification system with B-SECURUS
- › BAUER PLC based controller with 7” color HMI touchscreen display
- › NEMA 4 rated electrical enclosure with UL® listed control panel
- › Compressor low oil pressure and high temperature safety shutdowns
- › Emergency stop push button and automatic start/stop control
- › Zero loss automatic condensate drain system with non-corrosive condensate reservoir and integrated float sensor and automatic “Full” indication and compressor shutdown
- › Interstage pressure gauges (locally mounted)
- › Vertically hinged front operations panel and lift-off side maintenance access doors
- › Inlet filter maintenance indicator
- › Unique hinged front operations panel

AVAILABLE ACCESSORIES (FACTORY INSTALLED)

- › CO monitoring system
- › B-Kool (floor mount only)
- › H₂S monitoring system with audible alarm

SYSTEM FOOTPRINT

- VERTICUS:**
VAC5 - VAC26
DIMENSIONS L X W X H inches (mm)
› 55” x 35” x 70” (1397mm x 737mm x 1778mm)
WEIGHT pounds (kg)
› 1000 - 1400 lb (453.6 - 635 kg)



TECHNICAL DATA

Model	Charging Rate¹		Number of Stages	Motor		FAD²	RPM	Purification System
	SCFM	L/MIN		HP	kW			
5000 PSIG (345 BAR)								
VAC8-E1/E3	8.4	238	3	7.5	5.6	7	1250	P2 B-SECURUS
VAC20-E3	21	595	4	15	11	17.5	1300	P5 B-SECURUS
VAC26-E3	26.4	748	4	20	15	22	1350	P5 B-SECURUS
6000 PSIG (414 BAR)								
VAC5-E1/E3	5	142	3	5	3.7	4	1050	P2 B-SECURUS
VAC10-E1/E3	9.7	275	4	7.5	5.6	8.1	1180	P2 B-SECURUS
VAC13-E1/E3	13	368	4	10	7.5	10.8	1420	P2 B-SECURUS
VAC18-E3	18	510	4	15	11	15	1325	P5 B-SECURUS
VAC25-E3	25.2	714	5	20	15	21	1300	P5 B-SECURUS

1) Based on recharging an 80 cubic foot tank from 500 to 3000 psig.
2) Compressor capacity referenced to standard inlet conditions.
3) 30 HP units are in a cabinet other than depicted.
E1= Single phase electric, 230 VAC/60 Hz. E3=Three phase electric, 208/230/460 VAC/60 Hz. Other voltages available on request. Dimensions and weight are approximate and are subject to change.