Now at your dealer or **wh.com**



Easy and flexible.

Respects your needs. Today and tomorrow.





40 000

For **placing** implants



Thread cutter function

The automatic thread cutter function supports you when inserting implants.



Measure ISQ (Implant Stability Quotient)

The Implantmed SI-1015 can be upgraded at any time with the Osstell ISQ module or the Osstell Beacon, available as an accessory.



Stability measurement with SmartPeg

A new, sterile, single-use SmartPeg is screwed into the implant and made to resonate using the Osstell probe. The smaller the micromovements, the higher the ISQ value and the more stable the implant.



LOW ISQ		MEDIUM ISQ	HIG	HIGH ISQ	
	 60	 65	 70		



For your **work process**

Implantmed impresses users with its self-evident user interface.



Focusing on the essentials

The display shows the most important functions during treatment.




Self-evident simple to use

Colour touch screen with user-friendly menu guidance and glass surface.



Implantmed with new pump design!



Documentation

The documentation function saves all torque values during the implant insertion on a USB flash drive.



Ideal for the group practices

Customize Implantmed for multiple surgeons and their multiple individual drill protocols.



For the dental assistant

The new pump design allows quick loading of the irrigation tubing.



professional assistant for oral surgery, Germany

»The pump of the W&H Implantmed is incredibly easy to operate.«



new user interface

The new surgical straight and contra-angle handpieces with **mini-LED+**

WS-75 L | 20:1

Specially designed for preparation of the implant site and implant insertion.

S-11 L | 1:1

For apical resection, osteotomy, sequestrotomy, bone modelling and bone smoothing and also for

extraction of wisdom teeth.

WS-91 L | 1:2,7 45°-head Specially designed for extraction of wisdom teeth.

WS-56 L | 1:1 WS-92 L | 1:2,7 For osteotomy, sequestrotomy, germectomy, hemisection.

Whether you are inserting an implant or extracting a wisdom tooth, W&H offer a solution for each application. W&H surgical straight and contra-angle handpieces are made from high-quality stainless steel with a scratch-resistant coating.

Nicholas Claydon BDS MscD PhD MJDF RCS (eEng) FHEA

oral surgeon, UK

»Beautifully machined for quality and balance. Superb LED light that set a benchmark for visibility.«





Ergonomic balance

The contra-angle handpiece is comfortable in the hand and in combination with the ultra-short EM-19 electric motor perfectly balanced.

Flexible

Wireless foot control for controlling multiple W&H devices, such as Implantmed and Piezomed.



One for all

Control the functions of the Implantmed and Piezomed with only one foot control.

wireless!



Freedom of movement

With the wireless foot control you can select the optimum position in the work area without restrictions. No cables – no tangling – no mess.

Prof. Dr. José Luis Calvo Guirado D.D.S, PhD, Eu PhD, M.S.

oral surgeon, Spain

»Incredible easy to use in between the Implantmed and the Piezomed.«

The solution for your **implant workflow**



Osteotomy

6.2 Ncm for all bone qualities and 90 ml/min coolant to prevent necrosis.

Threading

Supports you when inserting implants.



ISQ

Implant insertion

The automatic torque control allows adjustment from 5 to 80 Ncm.

Measure ISQ

The Implantmed SI-1015 can be upgraded at any time with the W&H Osstell ISQ module and the Osstell Beacon, available as an accessory.



Documentation

Inform referrers about the torque and ISQ values or present your results to specialist audiences.

W&H accessories



Irrigation tubing

- Precise fit
- Time-saving for your dental assistants
- Original accessory for your Implantmed



W&H Impex transportation case

- Space for Implantmed, foot control, W&H Osstell ISQ module, straight and contra-angle handpieces
- › Also available for Piezomed

8

Implantmed Plus with ioDent® system

Implantmed Plus offers a surgical device that includes the unique »ioDent® system«. The intelligent W&H solution will increase safety in the practice and resources can be planned in advance to increase efficiency.



Easy data management

Share information with other clinicians or with patients.



Plan your operation

You can plan your operation in advance with the »Online Treatment Setup« and transmit the configuration to your Implantmed Plus. An integrated implant manufacturer database* sets all parameters before the operation.

* W&H Dentalwerk Bürmoos GmbH accepts no liability for ensuring that the information is up to date, correct and complete.

Traceability and safety

The USB stick is a thing of the past! Trace your surgical procedures with the »Online Documentation Protocol« - completely automatic, easy and secure.









ioDent® Gateway mini

The gateway is the link between your devices and the online platform. The number of connected devices is unlimited.

Always up-to-date

You will always be state-of-the-art with the functional extensions on the ioDent® online platform.



Personal Online Dashboard

Whether device status or required service: »Online Device Monitoring« provides you with an overview of your connected devices.



Technical data

C € 0297

Type:	Implantmed SI-1015		
Mains voltage:	120 V		
Permissible voltage fluctuation:	110 – 130 V		
Rated current:	0.3 – 1.6 A		
Frequency:	50 – 60 Hz		
Mains fuse (2 pcs):	250 V – T1.6AH		
Maximum power consumption:	170 VA		
Maximum power output:	80 W		
Maximum torque at motor:	6.2 Ncm		
Motor speed range in the rated voltage range:	200 – 40,000 min ⁻¹		
Coolant flow volume at 100%:	at least 90 ml/min		
Dimensions in mm (height x width x depth):	100 x 262 x 291		
Weight in kg:	3.5		
Foot control:	S-N2 / S-NW		
Straight and contra-angle handpieces with mini LED+:	S-11 L / WS-56 L, WS-75 L, WS-91 L, WS-92 L		
Warranty:	24 months		



Manufacturer:

W&H Dentalwerk Bürmoos GmbH

Ignaz-Glaser-Straße 53, Postfach 1 5111 Bürmoos, **Austria t** +43 6274 6236-0 **f** +43 6274 6236-55 office@wh.com **wh.com**

Distribution:

W&H Impex Inc.

6490 Hawthorne Drive
Windsor, Ontario, N8T 1J9
t 1 800 265 6277 Within USA/Canada
t 1.519.944.6739 Outside USA/Canada
f 1.519.974.6121
wh.com/na