

6.72" Adaptive Frequency



Display Technology	AM-OLED
Resolution(pixel)	1236×2676
Pixel Configuration	Windmill
PPI	438
Refresh Frequency	30-120HZ
Flicker@30HZ	<-45dB
TFT Type	LTPS
Application	Smart Phone

6.67 " HTD



Contrast Ratio	1400×3200
PPI	526
Contrast Ratio	>5000000:1
Refresh Rate	1~120HZ
Flicker (1Hz)	Support
Application	Smart Phone

8.03" TPOT Foldable AMOLED



Display Technology	AM-OLED
Resolution (pixel)	2000×2544
Pixel Configuration	YYG
PPI	403
Brightness (cd/m²)	600
Contrast Ratio	6000000:1
NTSC	DCI-P3 100% Cover(CIE1931)
Frame Rate (HZ)	60/90
Folding Type	V-type (Inner)
Radius (mm)	1.4
Angle	0~180°
Folding Endurance	≥200,000 Times
Cover Film	30um UTG
Application	Smart Phone

8.03" TPOT Rollable AMOLED



Display Technology	AM-OLED
Resolution (pixel)	2000×2544
Pixel Configuration	YYG
PPI	403
Brightness (cd/m²)	600
Contrast Ratio	6000000:1
NTSC	DCI-P3 100% Cover(CIE1931)
Frame Rate (HZ)	60/90
Folding Type	Roll-able
Radius (mm)	7
Folding Endurance	≥100,000 times
Application	Smart Phone

6.2" Static MLP



Display Technology	AM-OLED
Resolution (pixel)	876×2142
Pixel Configuration	YYG
PPI	373
Brightness (cd/m²)	420
Contrast Ratio	>100000:1
NTSC	>108%
EL Power Consumption	10~15% Reduction
Application	Smart Phone

6.55" Static MLP



Display Technology	AM-OLED
Resolution (pixel)	1080×2400
Pixel Configuration	SPR YYG
PPI	402
Brightness (cd/m²)	500
Contrast Ratio	>100000:1
NTSC	125%
EL Power Consumption	10~15% Reduction
Application	Smart Phone

6.67" Four Sides Curved AMOLED



Display Technology	AM-OLED
Resolution (pixel)	2340×1080
PPI	387
Brightness (cd/m²)	500
Contrast Ratio	1000000:1
NTSC	105%
Viewing Angle(U/D/L/R)	60/60/38/38
Border(L/R/U/D)(mm)	1.84/1.84/1.83/2.81
Application	Smart Phone

8.03" CFOT Rollable AMOLED



Display Technology	AM-OLED
Resolution (pixel)	2000×2544
Pixel Pitch(um)	63×63
PPI	403
Aperture Ratio	17.3%
Color Gamut (DCI-P3)	127%
Folding Type	Rollable
Radius (mm)	7
R%	4.5%
Power Reduction	20%
Application	Smart Phone

1.43 AMOLED



Display Technology	AM-OLED
Resolution(pixel)	466×466
PPI	326
NBM (cd/m ²)	600
HBM (cd/m ²)	>1000
Contrast Ratio	>1000000:1
Low Power Consumption	Balance Voltage
Flicker	Invisible @AOD 15Hz
CG Mode	3D Inside & Outside
Application	Wearable

1.53" Flexible AMOLED



Display Technology	AM-OLED
Resolution(pixel)	460×188
PPI	326
Contrast Ratio	>100000:1
Refresh Rate	30Hz-60Hz
Flicker (1Hz)	-40dB
Border (L/R/D) (mm)	1.034/1.034/1.616
Normal Mode	110mW
HBM(cd/m²)	950
Application	Wearable