

We Offer Customized Support to Fit Your Needs

- Add privacy and soften the environment with custom printed films & interlayers from our in-house Print Division
- Rely on a dedicated support staff with over three decades of experience to help you solve challenges— and take advantage of opportunities.

Contact Your Representative



Chad Snyder *Director of Security Products / Senior Specification Consultant*

• Email: defend@mcgrory.com

• Cell: 724-290-3136

McGRORYGLASS





Protect with fire-rated, attack-resistant glazing that's tested to meet top security standards.

PERFORMANCE & STANDARDS

Forced Entry Performance

- ASTM F 1915 Grade 1-4 (10-60 minutes of Forced Entry Resistance)
- HP White TP-.0500.03
- ASTM F1233

Fire Rated Performace

- ASTM E119
- UL263
- 60-90 Minute Heat Barrier

UL263 / ASTM E119 Security Glazing Testing



Pre-Test



Mid-Test



Post-Test



Protect with fire-rated, attack-resistant glazing that's tested to meet top security standards.

PERFORMANCE & STANDARDS

Forced Entry Performance

- ASTM F 1915 Grade 1-4 (10-60 minutes of Forced Entry Resistance)
- HP White TP-.0500.03
- ASTM F1233



ASTM F1233 Testing

Available with DotView™ One-Way Vision



Shown here in a dayroom application, our proprietary one-way vision privacy film offers transparency from the corridor view, but opacity from the dayroom view.

